



Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: FG54 Hi Temp Chainlube Aerosol (Food Grade)

Product Code: 7254

Uses: Adhesive lubricant spray for chains subject to high temperatures.

Company: Chemz Limited

Address: 80 Rangitane Place

Whakatu, Hastings

Telephone: +64 6 877 9690

Email: info@chemz.co.nz

Emergency Number 24 hr: 0800 764 766 (0800 POISON) National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes.

HSNO Classifications: GHS Classifications:

2.1.2A	Flammable aerosol	Flammable aerosol	Category 1
6.3A	Mildly irritating to the skin	Skin irritation	Category 2
6.9B	Harmful to human target organs or systems (narcotic)	STOT (repeated exposure)	Category 3
9.1B	Toxic to the aquatic environment with long lasting effects	Aquatic toxicity (chronic)	Category 2







Signal Words: Danger

Hazard Statements

H222 Extremely flammable aerosol

H315 Causes skin irritation

H336 May cause drowsiness or dizziness

H411 Toxic to aquatic life with long lasting effects

Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Hexanes	64742-49-0	30 - 60
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	10 - 30
Non Hazardous Ingredients		to 100

Ref: FG54 Hi Temp Chain Lube FG Aero 7254 Date: 9.11.20 Supersedes: 20.8.15 Issue No: 3 Page 1 of 5 pages





Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE 0800 764 766 or doctor.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice.

Skin contact: IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.

Inhalation: IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for

breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.

Ingestion: IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is

risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs.

Obtain immediate medical attention.

Notes to physician: Treat symptomatically and supportively. No specific antidote.

Section 5 - FIRE-FIGHTING MEASURES

General fire hazards: Pressurised container, extremely flammable aerosol.

Specific hazards: Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an

explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float

and be re-ignited on surface water.

Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to

wear self-contained breathing apparatus if risk of exposure to products of combustion.

Extinguishing media: For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.

For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight

streams of water.

Protective equipment: Firefighters must use standard protective equipment including flame retardant coat, helmet with face

shield, gloves, rubber boots, and in enclosed spaces, SCBA.

Fire fighting instructions: In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move

containers from fire area if you can do so without risk. Runoff can cause environmental damage.

Hazchem Code: 2YE

Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills: Clean up all spills immediately. Spills are extremely slippery. Remove all sources of ignition. If safe to do,

damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has

dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation.

Major spills: Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. Spills are extremely slippery.

If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly

labeled containers for disposal.

Section 7 - HANDLING AND STORAGE

Handling Precautions: Read product label before use. Keep out of reach of children.

This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even

after use.

Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.

Storage: Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool,

dry place. Keep away from heat, sparks, and flame. Store locked up.

Ref: FG54 Hi Temp Chain Lube FG Aero 7254 Date: 9.11.20 Supersedes: 20.8.15 Issue No: 3 Page 2 of 5 pages





Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits: No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
Hexanes	1,200	-
LPG (Liquefied petroleum gas – butane, propane)	1,800	-

Additional Information: Wash hands before eating, drinking and smoking.

Engineering Controls: No controls required when handling small quantities. Use with adequate ventilation.

Larger quantities: General exhaust is adequate under normal operating conditions. Ventilation

equipment and lighting should be explosion-resistant.

Protective Equipment: Generally not required for small quantities. In an industrial environment: gloves, safety glasses or

chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work

clothing should not be allowed out of the workplace.

In case of inadequate ventilation wear respiratory protection. If TWA is exceeded, wear an approved

respirator with a type A filter.

Section 9 - PHYSICAL AND CHEMICAL PROPERTIES

Physical state: Clear viscous liquid spray.

pH: Not applicable.

Vapour Density: > 1 (Air = 1)

Vapour Pressure, kPa: 300 - 600

Boiling Point, °C: About 60

Melting Point, °C: Not applicable.

Specific Gravity: About 0.7

Flash Point, °C: < 0 (propellant)

Explosion Limit, % v/v: LEL 1.2% UEL 9.5%

Autoignition Temp, °C: 443

Solubility: Not soluble in water.

Section 10 - STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity: Not toxic. LD₅₀ estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).

Acute Dermal Toxicity: Not toxic. LD₅₀ estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).

Acute Inhalation Toxicity: Not toxic. LC₅₀ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture). Inhalation of

vapours may cause drowsiness (narcotic) and dizziness.

Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.

Skin Irritation: Prolonged/repeated contact may cause defatting of the skin and dermatitis.

Eye Irritation: Spray is irritating to the eye. Expected to be reversible in less than 7 days.

Respiratory Irritation: Inhalation of vapours or mists may cause irritation to the respiratory system.

Ref: FG54 Hi Temp Chain Lube FG Aero 7254 Date: 9.11.20 Supersedes: 20.8.15 Issue No: 3 Page 3 of 5 pages





Sensitisation: Not expected to be a sensitiser.

Repeated Dose Toxicity: Prolonged skin contact with product may result in irritant contact dermatitis.

Additional Information: None of the components present in this material at concentrations equal to or greater than 0.1% are

listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity: Ecotoxic in the aquatic environment with long lasting effects.

Mobility: Low soil mobility.

Persistence/degradability: Not determined.

Bioaccumulation Potential: Not determined.

Section 13 - DISPOSAL CONSIDERATIONS

Material Disposal: Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the

environment, in drains or in water courses.

Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of

pressurised aerosols in landfills. Incineration in an authorised facility is suggested.

Container Disposal: Recycle empty container if possible or place in refuse waste stream. Product containers are also

considered wastes of the same class of the contents and should be disposed of in accordance with

applicable regulations.

Section 14 - TRANSPORT INFORMATION

Transport: Classified as a Dangerous Good for transport purposes.

Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7.

They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.

Proper Shipping Name: Aerosols

Dangerous Goods Class: 2.1

UN Number:

Transport Labels Required: Class 2 Flammable (Land, Sea and Air), EHSM (Sea and Air)

Land, Sea, Air Sea, Air



1950



Subsidiary Risk: Not applicable

Packing Group: Not applicable

Marine Pollutant: Yes

EMS Number F-D, S-U (UN 1950 Flammable aerosols)

DG Segregation: This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous

Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Section 15 – REGULATORY INFORMATION

EPA Approval Number: HSR002515 Aerosols (Flammable) Group Standard 2017.

Inventory Listing NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

Ref: FG54 Hi Temp Chain Lube FG Aero 7254 Date: 9.11.20 Supersedes: 20.8.15 Issue No: 3 Page 4 of 5 pages





This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data **SDS** regulations

Sheets) Notice July 2017.

EPA Hsno Controls: Refer to www.epa.govt.nz for information on Controls.

This substance is to be managed using the conditions specified in an applicable Group Standard.

Section 16 - OTHER INFORMATION

Additional information

Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations **AICS** Australian Inventory of Chemical Substances

> ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

CAS Chemical Abstract Service number

EMS Emergency Response Procedures for Ships Carrying Dangerous Goods

EPA Environmental Protection Agency GHS **Globally Harmonized System**

IARC International Agency for Research on Cancer

IATA International Air Transport Association **IMDG** International Maritime Dangerous Goods

 LC_{50} Lethal Concentration, 50% / Median Lethal Concentration

 LD_{50} Lethal Dose, 50% / Median Lethal Dose

LEL Lower Explosion Limit

mg/m³ Milligrams per Cubic Metre

NZIoC New Zealand Inventory of Chemicals

N.O.S. Not otherwise specified OEL Occupational Exposure Limit PEL Permissible Exposure Limit STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure) STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value TWA Time Weighted Average UEL **Upper Explosion Limit**

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of msds.

Ref: FG54 Hi Temp Chain Lube FG Aero 7254 Date: 9.11.20 Supersedes: 20.8.15 Issue No: 3 Page 5 of 5 pages