

CHEMZ FG24 BELT GRIP

Part No. 7224 (400ml)

Eliminates belt slippage

- Suitable for incidental food contact
- A tacky formulation which adheres strongly to belts assisting transmission efficiency and drive
- The product penetrates the cord fibres to restore pliability and flexibility
- Assists in power transfer and increases belt life.
- Suitable for both indoor and outdoor belt applications irrespective of humidity or temperature
- Keeps belts flexible, pliable and resistant to cracking

CHEMZ FG24 can be used on all types of belts, flat, round or V belts

CHEMZ FG24 can be used on belts made of rubber, leather, plastic or canvas

CHEMZ FG24 non-staining and contains no resins, asphalts or mineral oil

CHEMZ FG24 increase pulling power of belt



PERFORMANCE CHARACTERISTICS

Appearance	Clear, colourless, viscous liquid
Type of Film	Tacky, non-drying, water resistant film
Boiling Point, Initial °C	58
Temperature Range, °C	- 20 to + 170


AEROSOL PROPERTIES

Specific Gravity	0.63
Flash Point, °C	< 0
Propellant	Hydrocarbon

Storage/Shelf Life is 5 years if stored correctly
Empty aerosol container to be disposed of via metal scrap



Nonfood Compounds Program Listed H1
Registration No.152122



Ref #H3570 (approved for food/
beverage/dairy farm and factory)

MPI C26

(approved for use in premises processing
all animal product except dairy)



FOOD GRADE