



**GHS Classifications:** 

# **SAFETY DATA SHEET**

#### Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	Number 8 HandyLube Liquid
Product Code:	7388, 7389 & 7380
Uses:	Lubricant liquid to displace moisture and prevent corrosion.
Company:	Chemz Ltd
Address:	80 Rangitane Place
	Whakatu, Hastings
Telephone:	+64 6 877 9690
Email:	info@chemz.co.nz
Emergency Number, 24 hr:	0800 764 766 (0800 POISON) NZ National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

#### **Classification of the product**

Considered as a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes (land, sea and air).

#### **HSNO Classifications:**

3.1B	Flammable Liquids: high hazard	Flammable Liquids	Category 2
6.1E (Asp)	Acutely toxic (aspiration)	Aspiration hazard	Category 1
6.3A	Irritating to the skin	Skin irritation	Category 3
6.9B (Narc)	Harmful to human target organs or systems (narcotic)	STOT (single exposure)	Category 3
9.1C	Harmful in the aquatic environment with long lasting effects	Aquatic toxicity (Chronic)	Category 3



Signal Words: Danger

### **Hazard Statements**

H225	Highly flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H336	May cause drowsiness or dizziness (Narcotic).
H411	Toxic to aquatic life with long lasting effects.

#### Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
White Spirits (LAWS)	64742-82-1	30 - 60
Naphtha (petroleum), hydrotreated	64742-48-9	10 -30
Mineral Oil	8012-95-1	10 - 30
Other ingredients determined to not be hazardous	-	to 100%

Ref: Ezy Shine Liquid 7879





### Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is risk of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain immediate medical attention.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. Direct contact may cause irritation in sensitive individuals. If skin irritation occurs: Get medical advice/ attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.
Section 5 – FIRE-FIGHTIN	NG MEASURES
Specific hazards:	Containers can build up pressure if exposed to heat and may burst. Vapours may form an explosive mixture with air and can travel to a source of ignition and flash back. May be re-ignited on surface water.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion. Use water spray to keep fire-exposed containers cool.
Extinguishing media:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.
	For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment.
	Do NOT use straight streams of water.
Hazchem Code:	3YE
Section 6 – ACCIDENTAL	RELEASE MEASURES

Minor spills:	Spills are extremely slippery. Clean up all spills immediately. Remove all sources of ignition. If safe, damaged containers should be placed in a container outdoors, away from all ignition sources. Provide ventilation.
Major spills:	Spills are extremely slippery. Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

### Section 7 – HANDLING AND STORAGE

Handling Precautions:	Read product label before use. Keep out of reach of children. This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do
	not use near an open flame or other ignition source.
	Use outdoors or in well-ventilated area. Avoid breathing vapour. Wash hands with soap and water after handling.
Storage:	Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Keep container tightly closed. Store locked up.





## Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

	Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
	Naphtha, hydrotreated (supplier)	1200	1,600
	White Spirits (LAWS) (supplier)	350	-
	Mineral Oil (oil mist)	5	10
Additional Information: Engineering Controls:	Wash hands before eating, drinking and smoking. No controls required when handling small quantiti Larger quantities: General exhaust is adequate und and electrical equipment should be explosion-resis measures against static discharge.	der normal operating conditions. ۱	/entilation, lighting
Protective Equipment:	In an industrial environment: gloves, safety glasses or chemical goggles and protective gloves are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace. In case of inadequate ventilation wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.		

Physical state:	Clear colourless liquid.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	About 9
Boiling Point, °C:	About 75
Melting Point, °C:	Not applicable.
Specific Gravity:	About 0.8
Flash Point, °C:	< 0
Explosion Limit, % v/v:	LEL 1% UEL 7%
Autoignition Temp, °C:	> 200
Solubility:	Not soluble in water.

### Section 10 – STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

# Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.
Acute Oral Toxicity:	Low toxicity: $LD_{50}$ of mixture calculated to be > 5,000 mg/kg, Rat.
Acute Dermal Toxicity:	Low toxicity: $LD_{50}$ of mixture calculated to be > 5,000 mg/kg, Rabbit. Low toxicity
Acute Inhalation Toxicity:	High concentrations may cause drowsiness or dizziness and lead to central nervous system depression resulting in headaches and nausea.
Aspiration Hazard:	May be fatal if swallowed and enters airways.
Skin Irritation:	May cause skin irritation and defatting of the skin which can lead to dermatitis.





Eye Irritation:	Vapours may be irritating to the eye. Contact with eyes may cause short term discomfort.
<b>Respiratory Irritation:</b>	Inhalation of vapour may cause irritation to the nose and throat.
Sensitisation:	Not expected to be a sensitiser.
Repeated Dose Toxicity:	Central nervous system: repeated exposure may affect the nervous system. Prolonged contact with product may result in irritant contact dermatitis.
Additional Information:	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.

### Section 12 – ECOTOXICITY INFORMATION

Ecotoxicity:	Product is harmful to aquatic organisms with long lasting effects. Experimental data on the finished product are not available.
Mobility:	Floats on water. Volatile. Some components show low soil mobility.
Persistence/degradability:	Not readily biodegradable. Some components may be persistent.
Bioaccumulation:	Has the potential to bioaccumulate.

### Section 13 – DISPOSAL CONSIDERATIONS

Material Disposal:	Product wastes are ecotoxic and should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses. Waste product should not be allowed to contaminate soil or water. Large quantities should be handled by a suitable disposal facility. Incineration in an authorised facility is suggested.
Container Disposal:	Recycle empty container in an approved recycling stream. Product containers are considered wastes of the same class as the contents and should be disposed of in accordance with applicable regulations.

### Section 14 – TRANSPORT INFORMATION

Transport:	Classified as a Dangerous Good for transport purposes.		
Proper Shipping Name:	HYDROCARBONS, LIQUID, N.O.S. (contains Turpentine substitute, Naphtha (petroleum), hydrotreated)		
UN Number:	3295		
Dangerous Goods Class:	3		
Transport Labels Required:	Class 3 Flammable, Marine Pollutant		



Subsidiary Risk:	Not applicable	
Packing Group:	III	
Marine Pollutant:	Yes	
EMS Number	F-E, S-D	
Limited Quantity:	1L	
DG Segregation:	This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.	

## Section 15 – REGULATORY INFORMATION

EPA A	pproval Number:
-------	-----------------

HSR002603 Lubricants (Flammable) Group Standard 2017





This substance is to be managed using the conditions specified in an applicable Group Standard.

SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.	
Inventory Listing: Approved Handler:	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed. Not required.	
	Required if > 250 L (in containers > 5 L).	
	Required if > 500 L (in containers up to 5 L).	
Tracking:	This substance is not a tracked substance.	
EPA Hsno Controls:	Refer to www.epa.govt.nz for information on Controls.	

#### Section 16 – OTHER INFORMATION

Additional information	Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.		
Abbreviations	AICS	Australian Inventory of Chemical Substances	
	ADG	Australian Code for the Transport of Dangerous Goods by Road and Rail	
	CAS	Chemical Abstract Service number	
	EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods	
	EPA	Environmental Protection Agency (New Zealand)	
	GHS	Globally Harmonized System	
	IARC	International Agency for Research on Cancer	
	ΙΑΤΑ	International Air Transport Association	
	IMDG	International Maritime Dangerous Goods	
	LC <sub>50</sub>	Lethal Concentration, 50% / Median Lethal Concentration	
	LD <sub>50</sub>	Lethal Dose, 50% / Median Lethal Dose	
	LEL	Lower Explosion Limit	
	mg/m³	Milligrams per Cubic Metre	
	NICNAS	National Industrial Chemicals Notification and Assessment Scheme (Australia)	
	NZIoC	New Zealand Inventory of Chemicals	
	N.O.S.	Not otherwise specified	
	OEL	Occupational Exposure Limit	
	PEL	Permissible Exposure Limit	
	STEL	Short-Term Exposure Limit	
	STOT-RE	Specific target organ toxicity (repeated exposure)	
	STOT-SE	Specific target organ toxicity (single exposure)	
	TLV	Threshold Limit Value	
	TWA	Time Weighted Average	
	UEL	Upper Explosion Limit	

This SDS summarises to our best knowledge at the date of issue, the chemical health and safety hazards of the material and general guidance on how to safely handle the material in the workplace. Since Chemz Ltd cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, assess and control the risks arising from its use of the material. If clarification or further information is needed, the user should contact their Chemz representative or Chemz Limited at the contact details on page 1. Chemz Limited's responsibility for the material as sold is subject to the terms and conditions of sale. End of sds.