



## **DATA SHEET**

#### 2Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	Coloured Zinc Primer Aerosol 400ml (Various colours)
Product Code:	7514 Orange, 7564 Red, 7574 Green, 7584 Blue, 7524 White,7594 Yellow
Uses:	Zinc-rich protection coating aerosol for bare metal
Company:	Chemz Limited
Address:	80 Rangitane Place
	Whakatu, Hastings
Telephone:	+64 6 877 9690
Email:	info@chemz.co.nz
Emergency Number 24 hr:	0800 764 766 (0800 POISON) National Poison Centre

## Section 2 – HAZARDS IDENTIFICATION

#### **Classification of the product**

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ.

Classified as a dangerous goods for transport purposes.

GHS Classifications:	HSNO C	lassifications:
Aerosol Category 1	2.1.2A	Flammable aerosol
Skin irritation Category 3	6.3A	Irritating to the skin
Eye irritation Category 2	6.4A	Irritating to the eye
Carcinogenicity Category 2	6.7B	Suspected human carcinogen
Reproductive toxicity Category 2	6.8B	Suspected human reproductive or developmental toxicant
Reproductive toxicity effects on or via lactation	6.8C	Toxic human reproductive or developmental effects on or via lactation
STOT (Single exposure) Category 2	6.9B	Harmful to human target organs or systems (Single exposure)
Aquatic toxicity (chronic) Category 2	9.1B	Ecotoxic in the aquatic environment with long lasting effects (chronic)



Signal Words: Danger

#### Hazard Statements

H222	Extremely flammable aerosol.
H229	Pressurised container: May burst if heated
H315	Causes skin irritation.
H319	Causes serious eye irritation.
H351	Suspected of causing cancer.
H361	Suspected of damaging fertility or the unborn child.
H362	May cause harm to breast-fed children.
H371	May cause damage to organs by inhalation or if swallowed.
H411	Toxic to aquatic life with long lasting effects.



# Trusted Aerosol Performance

## DATA SHEET

#### Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Acetone	67-64-1	30 - 60
Xylene	1330-20-7	10 - 30
Aromatic Hydrocarbon	64741-95-6	< 10
Hydrocarbon propellant (LPG - Propane, Butane)	68476-85-7	10 - 30
Non-hazardous ingredients		to 100

#### Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE (0800 764 766) or doctor.

Eye contact:	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Ingestion:	IF SWALLOWED: Call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.

## Section 5 – FIRE-FIGHTING MEASURES

General fire hazards	Pressurised, extremely flammable aerosol.
Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. May float and be re- ignited on surface water. Will burn if involved in a fire.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
Extinguishing media:	For small fires, use dry chemical, carbon dioxide, water spray or alcohol-resistant foam.
	For large fires, use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment.
	Do NOT use straight streams of water.
Protective equipment	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Firefighting instructions	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
Hazchem Code:	2YE

Minor spills:Clean up all spills immediately. Provide ventilation. Remove all sources of ignition. If safe, damaged cans<br/>should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated.<br/>Undamaged cans should be gathered and stowed safely.





## DATA SHEET

Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.
Section 7 – HANDLING A	ND STORAGE
Handling Precautions:	Read product label before use. Keep out of reach of children.
	This product is highly flammable. Keep away from heat and open flames/hot surfaces. No smoking. Do not spray on an open flame or other ignition source. Pressurised container: Do not pierce or burn, even after use.
	Use in a well-ventilated area. Avoid breathing spray. Wash hands with soap and water after handling.
Storage:	Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool, dry place. Keep away from heat, sparks, and flame. Store locked up.

## Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

```
Exposure Limits:
```

No value assigned for product. Exposure standards for constituents (NZ WES);

	Material	TWA, mg/m³	STEL, mg/m <sup>3</sup>
	Acetone	1,185 <sub>(bio)</sub>	2,375 <sub>(bio)</sub>
	Xylene	217	-
	LPG (Liquefied petroleum gas – butane, propane)	1800	-
	(bio) - Exposure can also be estimated by biological monitoring.		
Additional Information:	Wash hands before eating, drinking and smoking.		
Engineering Controls:	No controls required when handling small quantities. Use outdoors or with adequate ventilation.		
	Larger quantities: General exhaust is adequate under nor equipment and lighting should be explosion-resistant.	mal operating conditions.	Ventilation
Protective Equipment:	Generally not required for small quantities. In an industrial environment: gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.		
	In case of inadequate ventilation wear respiratory protec respirator with a type A filter.	tion. If TWA is exceeded,	wear an approved

### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Coloured spray, solvent odour.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	300 - 600
Boiling Point, °C:	Not applicable.
Melting Point, °C:	Not applicable.
Specific Gravity:	Not applicable.
Flash Point, °C:	< 0 (propellant)
Explosion Limit, % v/v:	LEL 1.2% UEL 9.5%
Autoignition Temp, °C:	Not applicable.
Solubility:	Not soluble in water.





## **DATA SHEET**

## Section 10 – STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

### Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.
Acute Oral Toxicity:	$LD_{50}$ estimated to be 3,47 mg/kg (based on component mixture, excluding propellant).
Acute Dermal Toxicity:	$LD_{50}$ estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).
Acute Inhalation Toxicity:	$LC_{50}$ estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).
	Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.
Skin Irritation:	May cause skin irritation. Prolonged/repeated contact may cause defatting of the skin and dermatitis.
Eye Irritation:	Spray may be irritating to the eye.
Inhalation:	Inhalation may cause drowsiness or dizziness. Inhalation will cause narcotic effects.
<b>Respiratory Irritation:</b>	Inhalation of vapours or mists may cause irritation to the respiratory system.
Sensitisation:	Product is not expected to be a sensitiser.
Mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Product is a suspected human carcinogen.
Reproductive toxicity:	Product is a suspected human reproductive or developmental toxicant.
Reproductive toxicity effects via lactation:	Product has toxic human reproductive or developmental effects on or via lactation.
Specific Target Organ Toxicity	: Harmful to human target organs or systems (Single exposure)
Repeated Dose Toxicity:	Prolonged contact with product may result in irritant contact dermatitis.
Section 12 – ECOTOXICITY	INFORMATION
Ecotoxicity:	Ecotoxic in the aquatic environment with long lasting effects.
Mobility:	Product is partially volatile and large proportion will rapidly evaporate to the air if released into water.
Persistence/degradability:	More volatile components are expected to degrade in air. Some components may be persistent and may bioaccumulate.
Section 13 – DISPOSAL CO	NSIDERATIONS
Material Disposal:	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
Container Disposal:	Recycle empty container if possible. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.
Section 14 – TRANSPORT I	NFORMATION
Transport:	Classified as a Dangerous Good for transport purposes.
	Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.



## **DATA SHEET**

Proper Shipping Name:	Aerosols	
UN Number:	1950	
Dangerous Goods Class:	2.1	
Subsidiary Risk:	Not applicable	
Packing Group:	Not applicable	
Transport Labels Required:	Class 2 Flammable (Land, Sea and Air), EHSM (Sea and Air)	
	Land, Sea, Air Sea, Air	



Marine Pollutant:	Yes
EMS Number	F-D, S-U (UN 1950 Flammable aerosols)
DG Segregation:	This product is classified as a Dangerous Goods. Please consult the Land Transport Rule: Dangerous Goods 2005, and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Section 15 – REGULATORY INFORMATION		
Inventory Listing	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.	
SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.	
EPA Approval Number:	HSR002517 Aerosols (Flammable, Carcinogenic) Group Standard 2020	
EPA Hsno Controls:	Refer to <u>www.epa.govt.nz</u> for information on Controls.	
	This substance is to be managed using the conditions specified in an applicable Group Standard.	
Section 16 – OTHER INFORMATION		
Additional information	Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.	

Abbreviations CAS **Chemical Abstract Service number** EMS Emergency Response Procedures for Ships Carrying Dangerous Goods EPA **Environmental Protection Agency** GHS **Globally Harmonized System** IARC International Agency for Research on Cancer IATA International Air Transport Association IMDG International Maritime Dangerous Goods  $LC_{50}$ Lethal Concentration, 50% / Median Lethal Concentration Lethal Dose, 50% / Median Lethal Dose  $LD_{50}$ LEL Lower Explosion Limit mg/m<sup>3</sup> Milligrams per Cubic Metre NZIoC New Zealand Inventory of Chemicals



## Trusted Aerosol Performance

## **DATA SHEET**

N.O.S.	Not otherwise specified
OEL	Occupational Exposure Limit
PEL	Permissible Exposure Limit
STEL	Short-Term Exposure Limit
STOT-RE	Specific target organ toxicity (repeated exposure)
STOT-SE	Specific target organ toxicity (single exposure)
TLV	Threshold Limit Value
TWA	Time Weighted Average
UEL	Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of sds.