



## Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name: Copper Anti-Seize Paste 500g

Product Code: 7475

**Uses:** High temperature anti-seize lubricant grease

Company: Chemz Limited

Address: 80 Rangitane Place

Whakatu, Hastings

**Telephone:** +64 6 877 9690

Email: info@chemz.co.nz

Emergency Number 24 hr: 0800 764 766 (0800 POISON) National Poison Centre

### Section 2 – HAZARDS IDENTIFICATION

#### Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes.

#### **GHS Classifications:**

Acute toxicity: Oral Category 4
Eye irritation Category 2
Skin sensitisation Category 1

Germ cell mutagenicity Category 1

STOT (repeated exposure) Category 2 (oral, inhalation)

#### **HSNO Classifications:**

6.1D Acutely toxic - Harmful (oral)

6.4A Irritating to the eye

6.5B Contact sensitiser

6.6A Known or presumed human mutagens

6.9B Harmful to human target organs repeated (oral)

### **Pictograms**





Signal Words: Danger

#### **Hazard Statements**

H302 Harmful if swallowed

H319 Causes serious eye irritation

H317 May cause an allergic skin reaction

H340 May cause genetic defects.

H373 May cause damage to organs through prolonged or repeated exposure (oral)

## Section 3 - COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
Paraffinic Mineral Oil, Highly Refined	64742-62-7	> 60
Copper Powder	7440-50-8	10 - 30

## Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE 0800 764 766 (0800 POISON) or doctor.

Ref: Copper Antiseize Paste 7475 Date: 14.6.21 Supersedes: 18.2.16 Issue No: 2 Page 1 of 5 pages





Ingestion: IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Where there is risk

of vomiting, lean person forward or place on left side to avoid aspiration of product into lungs. Obtain

immediate medical attention.

Eye contact: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to

do. Continue rinsing. If eye irritation persists: Get medical advice.

**Skin contact:** IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.

Inhalation: Not considered a normal route of entry. If INHALED: If breathing is difficult, remove to fresh air and keep at

rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or

doctor.

**Notes to physician:** Treat symptomatically and supportively. No specific antidote.

### Section 5 - FIRE-FIGHTING MEASURES

General fire hazards: Combustible. The major hazard in fires is usually inhalation of heated and toxic or oxygen deficient (or both)

fire gases. There is no risk of an explosion from this product under normal circumstances if it is involved in a

fire.

Further advice: On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to

wear self-contained breathing apparatus if risk of exposure to products of combustion.

**Extinguishing media:** Suitable extinguishing media are carbon dioxide, dry chemical, foam and water fog. Do not discharge

extinguishing waters into the aquatic environment.

**Protective equipment:** Firefighters must use standard protective equipment including flame retardant coat, helmet with face

shield, gloves, rubber boots, and in enclosed spaces, SCBA.

**Fire fighting instructions:** Runoff can cause environmental damage.

Hazchem Code: 2YE

# Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills: Spills will be extremely slippery. Minor spills do not normally need any special cleanup measures. Clean up

all spills immediately.

Major spills: Spills are extremely slippery. Evacuate the spill area. Call the Fire Brigade. Prevent spillage from entering

drains or water courses. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal. After spills, wash area preventing runoff from entering drains. If a significant

quantity of material enters drains, advise emergency services.

### Section 7 – HANDLING AND STORAGE

Handling Precautions: Read product label before use. Keep out of reach of children. Wash hands with soap and water after

handling.

**Store** in a well ventilated, cool, dry place.

## Section 8 - EXPOSURE CONTROLS/PERSONAL PROTECTION

**Exposure Limits:** No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m <sup>3</sup>	STEL, mg/m <sup>3</sup>
Oil Mist, Mineral	5	10
Copper (respirable dust as Cu)	0.01 <sub>(r)</sub>	-

Additional Information: Wash hands before eating, drinking and smoking.

Engineering Controls: No controls required when handling small quantities. Use with adequate ventilation.

Ref: Copper Antiseize Paste 7475 Date: 14.6.21 Supersedes: 18.2.16 Issue No: 2 Page 2 of 5 pages





General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion resistant.

explosion-resistant.

**Protective Equipment:** General protective gloves are recommended as product may cause an allergenic reaction. In an industrial

environment: chemical protective gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the

workplace.

In case of inadequate ventilation, wear respiratory protection. If TWA is exceeded, wear an approved

respirator with a type A filter.

### Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

**Physical state**: Copper flecked paste.

pH: Not applicable.
 Vapour Density: Not applicable.
 Vapour Pressure, kPa: Not applicable.
 Boiling Point, °C: Not applicable.
 Melting Point, °C: Not applicable.

Specific Gravity: About 0.9

Flash Point, °C: Not applicable.

Explosion Limit, % v/v: Not applicable.

Autoignition Temp, °C: > 250

**Kinematic Viscosity:** 165 mm<sup>2</sup>/sec @ 40°C

**Penetration Index:** 265 - 295 1/10 mm @ 25°C

Drop Point, °C: 250

**Solubility:** Insoluble in water.

### Section 10 - STABILITY AND REACTIVITY

Stability: Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

## Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment: Information given is based on product testing, and/or similar products, and/or components.

Acute Oral Toxicity:  $LD_{50}$  estimated to be > 2,000 mg/kg (based on component mixture). Acute Dermal Toxicity:  $LD_{50}$  estimated to be > 5,000 mg/kg (based on component mixture).

Acute Inhalation Toxicity:  $LC_{50}$  estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).

**Skin Irritation:** Prolonged/repeated contact may cause defatting of the skin and dermatitis. Avoid contact with skin.

Eye Irritation: Contact may be irritating to the eye.

Respiratory Irritation: Not classified as a respiratory irritant.

Sensitisation: Contains a contact sensitiser which may cause a skin reaction in predisposed individuals. Toxicological

checks with similar products have not revealed any skin sensitivity aggravation. Not expected to be a

respiratory sensitiser.

**Repeated Dose Toxicity:** Prolonged contact with product may result in irritant contact dermatitis. Avoid skin contact.

Mutagenicity: Product is classified as mutagenic. Although there is no data on the mutagenicity of copper in humans, in vivo

studies and mammalian system in vitro studies suggest that copper is a potential human mutagen.

Ref: Copper Antiseize Paste 7475 Date: 14.6.21 Supersedes: 18.2.16 Issue No: 2 Page 3 of 5 pages





**Carcinogenicity:** Not expected to be carcinogenic.

**Reproductive toxicity:** Not expected to be toxic.

Additional Information: None of the components present in this material at concentrations equal to or greater than 0.1% are listed

by IARC, NTP, OSHA or ACGIH as being carcinogens.

### Section 12 – ECOTOXICITY INFORMATION

**Ecotoxicity:** Slightly ecotoxic in the aquatic environment. No environmental hazard is anticipated with small volumes of

product, provided that it is handled and disposed of with due care and attention.

**Mobility:** Given its physical and chemical characteristics, the product has no soil mobility.

Persistence/degradability: Inherently biodegradable.

Bioaccumulation Potential: Bioaccumulation is unlikely.

## Section 13 - DISPOSAL CONSIDERATIONS

Material Disposal: Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the

environment, in drains or in water courses.

This product may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. If neither of these options is suitable, consider controlled incineration, or landfill.

Container Disposal: Recycle empty container if possible. Product containers are also considered wastes of the same class of the

contents and should be disposed of in accordance with applicable regulations.

# Section 14 – TRANSPORT INFORMATION

**Transport:** Not classified as a Dangerous Good for transport purposes.

Proper Shipping Name: Not applicable

UN Number: Not applicable

Dangerous Goods Class: Not applicable

Transport Labels Required: Not applicable

Subsidiary Risk: Not applicable

Packing Group: Not applicable

Marine Pollutant: Yes
EMS Number F-A, S-A

**DG Segregation:** This product is not classified as a Dangerous Goods.

# Section 15 - REGULATORY INFORMATION

Inventory Listing NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.

SDS regulations This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets)

Notice July 2017 (Amended April 2021).

EPA Approval Number: HSR002606 Lubricants, Lubricant Additives, Coolants and Anti-freeze Agents (Subsidiary Hazard) GS 2020

**EPA Hsno Controls:** Refer to <a href="www.epa.govt.nz">www.epa.govt.nz</a> for information on Controls.

This substance is to be managed using the conditions specified in an applicable Group Standard.

Ref: Copper Antiseize Paste 7475 Date: 14.6.21 Supersedes: 18.2.16 Issue No: 2 Page 4 of 5 pages





### Section 16 - OTHER INFORMATION

#### Additional information

Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.

Health Effects from Exposure: It should be noted that the effects from exposure to this product will depend on several factors including: frequency and duration of use; quantity used; effectiveness of control measures; protective equipment used and method of application. Given that it is impractical to prepare a report which would encompass all possible scenarios, it is anticipated that users will assess the risks and apply control methods where appropriate.

Abbreviations

CAS Chemical Abstract Service number

EMS Emergency Response Procedures for Ships Carrying Dangerous Goods

EPA Environmental Protection Agency
GHS Globally Harmonized System

IARC International Agency for Research on Cancer
IATA International Air Transport Association
IMDG International Maritime Dangerous Goods

LC<sub>50</sub> Lethal Concentration, 50% / Median Lethal Concentration

LD<sub>50</sub> Lethal Dose, 50% / Median Lethal Dose

LEL Lower Explosion Limit mg/m³ Milligrams per Cubic Metre

NZIoC New Zealand Inventory of Chemicals

N.O.S. Not otherwise specified
 OEL Occupational Exposure Limit
 PEL Permissible Exposure Limit
 STEL Short-Term Exposure Limit

STOT-RE Specific target organ toxicity (repeated exposure)
STOT-SE Specific target organ toxicity (single exposure)

TLV Threshold Limit Value
TWA Time Weighted Average
UEL Upper Explosion Limit

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product.

End of msds.

Ref: Copper Antiseize Paste 7475 Date: 14.6.21 Supersedes: 18.2.16 Issue No: 2 Page 5 of 5 pages