

CONVAS

TECHNICAL DATA SHEET | 7354


CONVAS High Purity, Low Viscosity Vaseline Lubricant

- Lubricates HRC fuses, links, and switchgear contacts
- Protects battery terminals from oxidation and corrosion
- Prolongs contact life and improves reliability
- Resists sulphides, salt contamination, and harsh environments
- High purity, acid-free, easy-to-apply spray



Safety Data Sheet

Dual Action Spray



Chemz ConVas is a high purity, petroleum based contact lubricant formulated for electrical protection and long term performance. Its low viscosity characteristics allow it to penetrate fine fractures on battery surfaces, helping contain corrosive fumes while protecting terminals from oxidation. The acid free formulation provides excellent corrosion resistance and is chemically neutral to most materials. Chemz ConVas lubricates and protects HRC fuses, links, switchgear, disconnects and contact surfaces, extending service life and maintaining conductivity. It is also ideal for cable terminals, screw connections, battery terminals and applications in telecommunications, aerial installations and slideway lubrication.



CHEMZ CONVAS

CODE: 7354

SIZE: 400ml

PROPELLANT: Hydrocarbon

CONTAINS: Isohexane > 60%

PRECAUTIONS: Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection are recommended. Avoid breathing spray. Use only in a well-ventilated area. Do not eat, drink or smoke when using this product.

DIRECTIONS: Shake can well before use. Hold upright and spray a light, even coat onto clean, dry surfaces from 15-20 cm away. Allow product to penetrate and form a protective film, do not wipe off. Re-apply periodically for continued lubrication and corrosion protection.

APPLICATIONS:

INDUSTRIAL & MANUFACTURING - Lubricates switchgear, fuse contacts, terminals and connections.

TRANSPORT & LOGISTICS - Protects battery terminals and electrical contacts

CONSTRUCTION & MINING - Lubricates disconnects and electrical components

RURAL & AGRICULTURAL - Protects battery posts and machinery wiring

MARINE & FISHING - Protects terminals and connections from corrosion

Appearance (Residual Film)	Opaque white paste
Solubility	Not soluble in water
Specific Gravity	0.70
Temperature Range, °C	-30 to +150
Flashpoint, °C (Residual Film)	> 200
Flashpoint, °C (Propellant)	< 0
Propellant	Hydrocarbon

MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road
Whakatu, Hastings, 4180 New Zealand
Phone: 06 877 9690

EMERGENCY CALL:

0800 764 766
NZ POISON CENTRE (24HR)



www.chemz.co.nz

