

# WHITE LITHIUM GREASE

## TECHNICAL DATA SHEET | 7424


### CHEMZ WHITE LITHIUM GREASE High Performance Complex Grease

- Multi-purpose white lithium complex grease
- Heavy-duty lubricant reduces friction and wear
- Superior performance in all weather conditions
- Protects against moisture, rust and corrosion
- Non-drip formula ideal for vertical surfaces




Safety Data Sheet

#### Dual Action Spray



**Chemz White Lithium Grease** is a high-performance, multi-purpose lubricant formulated with a lithium complex base for demanding industrial applications. With a high drop point of 280°C and advanced polymer treatment, it delivers long-lasting lubrication with excellent resistance to heat, water and corrosion. Its versatility helps reduce the need for multiple specialty greases, improving cost efficiency. Chemz White Lithium Grease performs reliably across all temperatures, stays in place without running or dripping and its white colour allows easy visual inspection during application.



### CHEMZ WHITE LITHIUM GREASE

**CODE:** 7424

**SIZE:** 400ml

**PROPELLANT:** Hydrocarbon

**PRECAUTIONS:** Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection (safety glasses or goggles) are recommended in an industrial environment. Avoid breathing vapours/spray. Use only in a well-ventilated area. In confined areas, use a respirator. Do not eat, drink or smoke when using this product.

**DIRECTIONS:** Shake the can well before use. Hold approximately 25 cm from the surface. Apply to a clean, dry surface for optimal performance.

#### APPLICATIONS:

**INDUSTRIAL & MANUFACTURING** - Lubricates slides, bearings, guide and moving assemblies

**TRANSPORT & LOGISTICS** - Protects hinges, latches, couplings and chassis

**CONSTRUCTION & MINING** - Lubricates pins, bushes, linkages, and mechanisms

**RURAL & AGRICULTURAL** - Protects gates, pivots, shafts, and farm equipment

**MARINE & FISHING** - Resists moisture on winches, hinges, and hardware

Appearance	Opaque off-white, viscous grease
Texture	Tacky
Thickener	Polymer fortified lithium complex
Water Resistance	Excellent
Heat Resistance	Excellent
NLGI Grade	2
Penetration Index , 1/10 mm at 25°C	275
Dropping Point, °C	280
Kinematic Viscosity, cSt at 40°C	144
Viscosity Index	53
Flash Point, °C	< 0
Propellant	Hydrocarbon

#### MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road  
Whakatu, Hastings, 4180 New Zealand  
Phone: 06 877 9690

#### EMERGENCY CALL:

**0800 764 766**  
**NZ POISON CENTRE (24HR)**



[www.chemz.co.nz](http://www.chemz.co.nz)

