



CHEMZ *Xtra Cutting Oil*

Part No. 7714 (400ml)

General purpose drilling and cutting lubricant

- Lubricates & cools efficiently
- Reduces friction & wear
- For use on ferrous & non-ferrous metals
- Improves surface finish



CHEMZ Xtra Cutting Oil is a high performance cutting lubricant which provides excellent wetting, penetrating and properties

CHEMZ Xtra Cutting Oil eliminates galling, seizing and extends tool life by lubricating and cooling efficiently

CHEMZ Xtra Cutting Oil gives superior results in all metal working operations by improving surface finish and reducing friction and wear

CHEMZ Xtra Cutting Oil can be used in all machining, drilling, reaming, threading and milling

CHEMZ Xtra Cutting Oil is suitable for all types of metal and can be used on ferrous and non-ferrous metals and alloys including copper and brass

CHEMZ Xtra Cutting Oil contains no mineral oil or water and requires less product than traditional cutting fluids

Technical Data

Appearance	Light amber oily liquid
Specific Gravity	0.90
Flash Point (oil), °C	202
Chlorine Additives	Chlorine free
Pour Point, °C	- 10
Copper Corrosion, 3 hours at 100°C	1B (maximum). Non-corrosive.
4 Ball EP Test, kg/cm ² (200 rpm)	6.5
Propellant	Hydrocarbon

MPI Approved C12 (All animal products except dairy)