

CABLE GLIDE

TECHNICAL DATA SHEET | 7344


Cable Glide Cable Pulling Lubricant

- High-quality cable pulling lubricant
- Reduces friction for easier horizontal and vertical pulls
- Compatible with all common cable types
- Acts as a moisture barrier, non-sticky
- Wide temperature range from -50°C to +200°C



Safety Data Sheet

Wide Top Mini Jet Spray



Chemz Cable Glide is a premium-grade cable pulling lubricant designed to ease cables through conduits, electrical trays, timber and wall boards. It reduces friction, speeds up installation and protects cable insulation from fraying, cracking, or breaking. Non-sticky and acting as an effective moisture barrier, Chemz Cable Glide is compatible with all common cable types and safe for plastics in everyday use. Its wide temperature range of -50°C to +200°C ensures reliable performance for both horizontal and vertical cable pulls, saving time and improving efficiency on every job.

CHEMZ CABLE GLIDE

CODE: 7344

SIZE: 400ml

PROPELLANT: Hydrocarbon

CONTAINS: Heptanes 30 – 60% W/W

MPI APPROVED C12 (All animal products except dairy)


APPLICATIONS:

PRECAUTIONS: Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection are recommended. Avoid breathing vapours/spray. Use only outdoors or in a well-ventilated area.

- INDUSTRIAL & MANUFACTURING** - Protects PCBs, relays, terminals and sensors
- TRANSPORT & LOGISTICS** - Coats wiring, connectors and control modules
- CONSTRUCTION & MINING** - Shields switches, motors and instrumentation
- RURAL & AGRICULTURAL** - Covers electrical panels, sensors and pumps
- MARINE & FISHING** - Protects marine electronics, wiring and masts

DIRECTIONS: Spray Chemz Cable Glide to surfaces of cables to be inserted into conduits.

Appearance	Clear, colourless liquid
Solubility	Not soluble in water, resists washout
Specific Gravity	0.87
Viscosity, cS at 20°C	1000
Temperature Range, °C	-50 to +200
Flashpoint, °C (Residual Film)	315
Flashpoint, °C (Propellant)	< 0
Propellant	Hydrocarbon



MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road
Whakatu, Hastings, 4180 New Zealand
Phone: 06 877 9690

EMERGENCY CALL:

0800 764 766
NZ POISON CENTRE (24HR)



www.chemz.co.nz

