

GRAPHITE


TECHNICAL DATA SHEET | 7455

CHEMZ GRAPHITE SWITCH PLATE LUBE Track and Rail Lubricant

- Graphite-based lubricant reduces wear on switchplates
- Resists rain, corrosion and contaminants
- Extreme pressure and anti-wear properties
- Wide temperature range -30°C to +140°C
- Leaves durable, strong thin film



Safety Data Sheet



Up Side
Down Nozzle

Chemz Graphite SPL is a specially formulated lubricant designed for use on rail industry switchplates. It provides a tough, long-lasting thin film that resists rain wash-off and can even be applied to wet surfaces, with the spray removing excess water. Chemz Graphite SPL offers excellent corrosion protection, resists contaminants and performs reliably across a wide temperature range. Its formulation ensures extreme pressure and anti-wear performance, making it ideal for maintaining switchplates under demanding rail operating conditions.



CHEMZ GRAPHITE SWITCH PLATE LUBRICANT

CODE: 7455

SIZE: 500ml

PROPELLANT: Hydrocarbon

PRECAUTIONS: Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection are recommended. Avoid breathing vapours/spray. Use only in a well-ventilated area. In confined areas, use a respirator. Do not eat, drink or smoke when using this product.

DIRECTIONS: Shake the can thoroughly before use. Ensure the surface is clean, dry, and free from grease. For best results, clean the surface with Chemz Electro Clean or Chemz Rapid Brakeclean before application.

APPLICATIONS:

INDUSTRIAL & MANUFACTURING - Lubricates heavy-duty sliding plates and exposed steel components

TRANSPORT & LOGISTICS - Reduces wear on rail metal interfaces

CONSTRUCTION & MINING - Protects high-load sliding contact points

RURAL & AGRICULTURAL - Lubricates steel contact points on machinery

MARINE & FISHING - Protects exposed metal from moisture

Colour	Dark grey liquid
Odour	Hydrocarbon solvent
Density	0.75 g/cm ³
Vapour Density	Heavier than air
Co-efficient of Friction	Low
Evaporation	Medium fast drying
Solids	> 30%
Type of Film	Dry film
Flash Point	< 0 °C
Propellant	Hydrocarbon

MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road
Whakatu, Hastings, 4180 New Zealand
Phone: 06 877 9690

EMERGENCY CALL:

0800 764 766
NZ POISON CENTRE (24HR)



www.chemz.co.nz

