

# PENETRENE

## TECHNICAL DATA SHEET | 7304

### CHEMZ PENETRENE Lubricates, Penetrates & Drives Out Moisture


- Suitable for all electrical and mechanical equipment
- Penetrates rusted parts and frees sticky mechanisms
- Prevents corrosion and oxidation long-term
- Forms a clear, invisible protective film
- Safe on plastics, rubber and paint



Safety Data Sheet



#### Dual Action Spray



Chemz Penetrene Multi is a versatile, multi-purpose product for electrical and mechanical applications. It penetrates rusted components, lubricates moving parts, eliminates moisture-related electrical shorts and protects against corrosion and oxidation.

Penetrene forms a clear, invisible film that is safe on plastics, rubber and painted surfaces. Suitable for workshops, farms, homes and hobbies, it is ideal for electronic equipment, ignition systems, bolts, hinges, engines, vehicles, roller doors, bicycles, lawnmowers, garden tools, marine equipment and sporting goods.

### CHEMZ PENETRENE

**CODE:** 7304

**SIZE:** 400ml

**PROPELLANT:** Hydrocarbon

**CONTAINS:** Aliphatic Hydrocarbon 30 - 60%

MPI APPROVED C12 (All animal products except dairy)

**APPLICATIONS:**

**PRECAUTIONS:** Extremely Flammable. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection are recommended. Avoid breathing spray. Use only in a well-ventilated area. Do not eat, drink or smoke when using this product.

**INDUSTRIAL & MANUFACTURING** - Protects electrical components, instruments, fasteners and moving equipment

**TRANSPORT & LOGISTICS** - Lubricates ignition systems and mechanical parts

**CONSTRUCTION & MINING** - Frees bolts, mechanisms and preventing corrosion

**RURAL & AGRICULTURAL** - Maintains tractors, engines and farm equipment

**MARINE & FISHING** - Prevents corrosion on metal parts, cleans and lubricates

**DIRECTIONS:** Spray on, do not wipe off. To guarantee full lubricating and corrosion protection repeat the procedure from time to time.

Appearance	Clear, colourless liquid
Odour	Mild, characteristic
Type of Film	Oily, wet
Dry Time	Non-drying wet oil
Specific Gravity	0.75
Temperature Range, °C	-10 to + 150
Kinematic Viscosity (oil), mm <sup>2</sup> /s 40°C	15 – 25
Corrosion Protection (Salt Spray)	Up to 500 hours
Falex Lubrication Test, hours	790
Propellant	Hydrocarbon

#### MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road  
Whakatu, Hastings, 4180 New Zealand  
Phone: 06 877 9690

#### EMERGENCY CALL:

**0800 764 766**  
**NZ POISON CENTRE (24HR)**



[www.chemz.co.nz](http://www.chemz.co.nz)

