

# CHEMZ FG64 HI-LO GREASE

Part No. 7264 (500ml)

## High performance extreme pressure food grade lubricant

- Suitable for incidental food contact
- Reduces friction and wear in metal to metal and metal to plastic applications
- Operates at both low and high temperatures

**CHEMZ FG64** can be used in variable retention tunnels, chillers and freezers -40°C

**CHEMZ FG64** can be used in ovens and steriliser bearings +180°C

**CHEMZ FG64** excellent EP performance and resistant to water and corrosion

PERFORMANCE CHARACTERISTICS	
Appearance	Opaque light brown, viscous grease
Type of Film	Non-drying, water resistant film
Temperature Range, °C	- 40 to + 180
Food Acids and Alkalis	Resistant to food acids and alkalis
Dropping Point, °C	> 300
Four Ball – Weld load, kgf	620
Anti-rust Performance SKF-EMCOR	0 - 0
NLGI Grade	1 – 2

AEROSOL PROPERTIES	
Specific Gravity	0.65
Flash Point, °C	< 0
Propellant	Hydrocarbon
Storage/Shelf Life is 5 years if stored correctly	
Empty aerosol container to be disposed of via metal scrap	



**NSF H1 APPROVED**

Nonfood Compounds Program Listed H1  
Registration No.152125

**AsureQuality**

Ref #H3572 (approved for food/  
beverage/dairy farm and factory)

**MPI C15**

(approved for use in premises processing  
all animal product except dairy)



# FOOD GRADE