

ZINC SILVER

TECHNICAL DATA SHEET | 7544

CHEMZ ZINC SILVER Zinc Rich Protection Coating


- Coloured zinc-rich coating for bare metal protection
- Electrochemically bonds to metal surfaces
- Corrosion and weather resistant finish
- Fast drying single component formulation
- Dries to bright, galvanised metallic appearance



Safety Data Sheet



Adjustable Fan Spray



Chemz Silver Zinc is a bright metallic, zinc-rich coating formulated to refinish damaged or repaired hot dipped galvanising and spot weld areas. The coloured film contains pure zinc complexes that electrochemically bond to bare metal, providing long-term corrosion protection in harsh environments. It delivers a fast-drying, durable finish that closely matches the appearance of new galvanising. When used as a finishing coat over Chemz Zinc #7533, it provides ultimate protective performance. For best results, apply to clean, dry surfaces, removing loose scale before surface preparation with Chemz Electro Clean Code #7125 or Chemz Rapid Brake Cleaner #7856.

CHEMZ ZINC SILVER

CODE: 7544

SIZE: 400ml

PROPELLANT: Hydrocarbon

MPI APPROVED C23 (All animal products except dairy)

PRECAUTIONS: Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection are recommended. Avoid breathing vapours/spray. Do not eat drink or smoke when using this product. Use only outdoors or in a well-ventilated area. In confined areas, wear a respirator. Use explosion-proof equipment.

DIRECTIONS: Chemz Zinc Silver should be applied to clean, dry, bare metal. Remove loose corrosion with a stiff brush or scraper, as galvanic protection relies on zinc bonding directly to metal. Shake can for 2 minutes after the ball rattles. Clean surfaces with Chemz Rapid before application. Apply one full coat, a second coat is recommended for added protection.

APPLICATIONS:

INDUSTRIAL & MANUFACTURING - Protects structural steel, frames and fabricated components

TRANSPORT & LOGISTICS - Touch-up protection for trailers, truck bodies, fittings

CONSTRUCTION & MINING - Protects steel structures and weld repairs

RURAL & AGRICULTURAL - Protects gates, machinery, and farm equipment

MARINE & FISHING - Protects metal surfaces in coastal environments

Colour	Silver
Touch Dry	15 - 30 minutes
Overcoat	4 hours plus
Completely Cured (20°C)	24 hours
Temperature Resistance, °C	Up to 120
Zinc Pigment Purity, % w/w	99.5
Corrosion Protection	Up to 5 years outdoors
Propellant	Hydrocarbon

MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road
Whakatu, Hastings, 4180 New Zealand
Phone: 06 877 9690

EMERGENCY CALL:

0800 764 766
NZ POISON CENTRE (24HR)



www.chemz.co.nz

