

# CARBZ & THROTTLE BODY

## TECHNICAL DATA SHEET | 7825

### CHEMZ CARBZ AND THROTTLE BODY CLEANER


- Cleans EGR valves and deposits, improves MPG
- No disassembly required for fast cleaning
- Dissolves gum, sludge, varnish, grease, and deposits
- Ensures maximum fuel economy and smooth performance
- Safe for catalytic converters



Safety Data Sheet



#### Dual Action Spray



**Chemz Carbz Throttle Body Cleaner** is specially formulated to quickly remove gum, sludge, varnish, paraffin, gasoline stains, grease and dirt build-up from carburetors, throttle bodies, automatic chokes, PCV and EGR valves. It effectively cleans linkages, choke shafts, camming surfaces, heat risers, hose and base fittings and fuel injection throttle body deposits without disassembly. Chemz Carbz helps reduce poor exhaust emissions, ensures smooth engine performance and is safe for catalytic converters, making it ideal for maintenance of automotive engines and fuel systems.

### CHEMZ CARBZ & THROTTLE BODY CLEANER

**CODE:** 7825

**SIZE:** 500ml / 450gm

**PROPELLANT:** Hydrocarbon

#### APPLICATIONS:

**INDUSTRIAL & MANUFACTURING** - Cleans machinery engines, fuel system components, and mechanical linkages

**TRANSPORT & LOGISTICS** - Degreases throttles, carburetors, PCV/EGR valves

**CONSTRUCTION & MINING** - Removes deposits from machinery fuel systems

**RURAL & AGRICULTURAL** - Cleans tractor engines and fuel system parts

**MARINE & FISHING** - Maintains boat engines and throttle components

**PRECAUTIONS:** Keep away from heat, sparks, flames, and hot surfaces. Do not spray on open flames or pierce/burn the can. Use outdoors or in well-ventilated areas. Avoid inhaling vapours or contact with eyes, skin, and clothing. Wear protective gloves and eye protection. Wash hands after use. Do not expose to sunlight or temperatures above 50°C. Seek medical advice if exposed or concerned.

**DIRECTIONS:** Ensure engine is off and cool. Shake can and spray CHEMZ CARBZ & Throttle Body Cleaner on carburetor exteriors, linkages, choke, and automatic choke parts. Let soak 1 minute, then respray to flush deposits. For PCV valves, disconnect, spray while shaking, let soak, then respray. For carburetor throats, start engine at fast idle and spray in short bursts until clean.

Appearance	Clear colourless mobile liquid
Odour	Characteristic, ketone solvent
Specific Gravity	0.77
Evaporation Rate	High
Volatile Components, % w/w	100
Flammability	Highly flammable
Flashpoint, °C (Propellant)	< 0
Propellant	Hydrocarbon

#### MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road  
Whakatu, Hastings, 4180 New Zealand  
Phone: 06 877 9690

#### EMERGENCY CALL:

**0800 764 766**  
**NZ POISON CENTRE (24HR)**



[www.chemz.co.nz](http://www.chemz.co.nz)

