

# EZY SHINE

## TECHNICAL DATA SHEET | 7876


### CHEMZ EZY SHINE Wet Look Tyre Shine

- Simple spray-on application, no brushing required
- Ultra-high gloss wet look finish
- Instantly cleans and shines tyres
- Safe on mudflaps, bumpers and wheels
- Prevents tyre colour disfiguration



Safety Data Sheet

#### Wide Top Conical Spray



**Chemz Ezy Shine** is an ultra-high gloss wet look tyre shine that delivers a perfect, long-lasting finish instantly. Its easy spray-on formula requires no brushing or wiping, making it the simplest and most effective way to clean and shine tyres, mudflaps, and bumpers. Chemz Ezy Shine is specially formulated to prevent tyre colour disfiguration while being safe on paint-work and wheels. Ideal for both low-profile and high-performance tyres, it leaves a durable, showroom-quality shine every time.



### CHEMZ EZY SHINE

**CODE:** 7876

**SIZE:** 600ml

**PROPELLANT:** Hydrocarbon

#### APPLICATIONS:

**PRECAUTIONS:** Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Gloves and eye protection are recommended. Avoid breathing vapours/spray. Use only in a well-ventilated area. In confined areas, use a respirator. Do not eat, drink or smoke when using this product.

**DIRECTIONS:** Shake can well. Chemz Ezy Shine should be sprayed in short bursts around the tyre. Cover with a liberal coating, any overspray should be wiped away with a soft cloth.

- ✓ **INDUSTRIAL & MANUFACTURING** - Cleans and shines forklift and warehouse vehicle tyres
- ✓ **TRANSPORT & LOGISTICS** - Maintains truck, van, and fleet tyre appearance
- ✓ **CONSTRUCTION & MINING** - Protects, shines heavy equipment and machinery tyres
- ✓ **RURAL & AGRICULTURAL** - Cleans tractor, harvester, and farm machinery tyres
- ✓ **MARINE & FISHING** - Maintains trailer and boat vehicle tyres in wet conditions

Appearance	Clear, colourless liquid spray
Odour	Characteristic, slight solvent
Solubility	Not soluble in water, resists washoff
Specific Gravity	0.80
Dry time	5 minutes
Temperature Range, °C	- 50 to + 200
Flashpoint, °C (Residual Film)	> 200
Flashpoint, °C (Propellant)	< 0
Propellant	Hydrocarbon

#### MANUFACTURED BY:

CHEMZ Limited, 80 Rangitane Road  
Whakatu, Hastings, 4180 New Zealand  
Phone: 06 877 9690

#### EMERGENCY CALL:

**0800 764 766**  
**NZ POISON CENTRE (24HR)**



[www.chemz.co.nz](http://www.chemz.co.nz)

