MX3 CHAIN LUBE

TECHNICAL DATA SHEET | 7652 7655

CHEMZ MX3 CHAIN LUBE

- Adhesive lubricant for chains, sprockets and pins
- Foaming, non-fling technology for long-lasting coverage
- Suitable for all types of O-Rings
- Reduces noise, wear and friction
- Wide temperature range -30°C to +180°C

Safety Data Sheet

Wide Top Mini Jet Spray



MX3 250ml

Dual Action Spray



MX3 500ml

Chemz MX3 Chain Lube is specially formulated for all motorcycle chains, providing deep penetration into inner pins, rollers and bushings. After the propellant evaporates, it thickens to form a durable, long-lasting lubricant that resists fling-off even at high speeds. Its additives reduce noise, friction and wear, helping to extend chain life. Safe for all types of O-Rings, Chemz MX3 Chain Lube performs reliably in extreme conditions, including hot, cold, and saltwater environments, making it ideal for both off-road and on-road use.

CHEMZ MX3 CHAIN LUBE

CODE : 7652 / 7655

SIZE : 250ml / 198gm
500ml / 395gm

PROPELLANT: Hydrocarbon

PRECAUTIONS: Read label before use. Keep out of reach of children. Wash hands thoroughly after handling. Safety glasses are recommended. Use only in a well-ventilated area. Do not eat, drink or smoke when using this product.

DIRECTIONS: Ensure the chain is clean, dry and free from contaminants. Shake the can thoroughly before use. Apply evenly to the inside of the chain while rotating the wheel. Allow time for the propellant to evaporate, leaving behind the ideal lubrication film.

APPLICATIONS:

INDUSTRIAL & MANUFACTURING - Lubricates chains, sprockets, pins and rollers in workshop bikes

TRANSPORT & LOGISTICS - Protects motorcycle and scooter chains

CONSTRUCTION & MINING - Lubricates off-road and utility bike chains

RURAL & AGRICULTURAL - Maintains ATV, tractor and farm bike chains

MARINE & FISHING - Protects chains and pins from corrosion and wear

Colour	Light amber
Odour	Characteristic, mild
Density	0.880 g/cm
Viscosity (oil)	150 mm^2/s (40°C)
Pour Point	- 12°C
Behaviour	Adhesive film
Temperature Range	-30°C to +180°C
Water Solubility	Negligible at 20°C
Flashpoint (Propellant)	< 0 °C
Flashpoint (Residual Film)	< 100 °C
Propellant	Hydrocarbon

MANUFACTURED BY:
CHEMZ Limited, 80 Rangitane Road
Whakatu, Hastings, 4180 New Zealand
Phone: 06 877 9690

EMERGENCY CALL:
0800 764 766
NZ POISON CENTRE (24HR)

NEW ZEALAND MADE

www.chemz.co.nz

CHEMZ

Application examples listed are typical uses only and are not intended to be exhaustive or limit the product's suitability.